

Pressure Tank



**Horizontal Type
Pressure Tank**

SPECIFICATION

Replaceable membrane pressure tank
Stainless steel flange
Working temperature:
Buytl: -20° C ~ 99° C
EPDM: -20° C ~ 99° C

Horizontal	Max. Working Pressure	Max. Working Temperature	Connector	Weight (kg)	Packing Dimension (mm)
19 Litre	10 bar /145 psi	99° C	½"	4.2	290 x 290 x 400
24 Litre	10 bar /145 psi	99° C	1"	4.5	290 x 290 x 465
36 Litre	10 bar /145 psi	99° C	1"	5.2	340 x 365 x 420
50 Litre	10 bar /145 psi	99° C	1"	6.5	340 x 365 x 500
60 Litre	10 bar /145 psi	99° C	1"	7.5	340 x 365 x 680
80 Litre	10 bar /145 psi	99° C	1"	13	390 x 420 x 780



**Vertical Type
Pressure Tank**

SPECIFICATION

Replaceable membrane pressure tank
Stainless steel flange
Working temperature:
Buytl: -20° C ~ 99° C
EPDM: -20° C ~ 99° C

Vertical	Max. Working Pressure	Max. Working Temperature	Connector	Weight (kg)	Packing Dimension (mm)
2 Litre	10 bar /145 psi	99° C	½"	-	-
5 Litre	10 bar /145 psi	99° C	1"	1.5	165 x 165 x 340
8 Litre	10 bar /145 psi	99° C	1"	1.8	210 x 210 x 340
19 Litre	10 bar /145 psi	99° C	1"	3.7	370 x 270 x 400
24 Litre	10 bar /145 psi	99° C	1"	4	340 x 340 x 340
24 Litre	10 bar /145 psi	99° C	1"	4	270 x 270 x 465
50 Litre	10 bar /145 psi	99° C	1"	6	340 x 340 x 550
60 Litre	10 bar /145 psi	99° C	1"	7	340 x 340 x 700
80 Litre	10 bar /145 psi	99° C	1"	12	390 x 390 x 780



**Vertical Type With
Feet Pressure Tank**

SPECIFICATION

Replaceable membrane pressure tank
Stainless steel flange
Working temperature:
Buytl: -20° C ~ 99° C
EPDM: -20° C ~ 99° C

Vertical	Max. Working Pressure	Max. Working Temperature	Connector	Height (mm)	Dimension (mm)
50 Litre	10 bar /145 psi	99° C	1"	592	333
60 Litre	10 bar /145 psi	99° C	1"	760	389
80 Litre	10 bar /145 psi	99° C	1"	780	389
100 Litre	10 bar /145 psi	99° C	1"	850	450
150 Litre	10 bar /145 psi	99° C	1"	1100	510
200 Litre	10 bar /145 psi	99° C	1 ½"	1100	590
300 Litre	10 bar /145 psi	99° C	1 ½"	1100	650

Authorized Dealer:
SAFEGWAY MARKETING PTE LTD
35 Kallang Pudding Road,
Blk A, #02-12, Tong Lee Building
Singapore 349314
Tel: 65-67442277 / Fax: 65-67445706
Email: safewaykl@lycos.com